



FN	PART NUMBER	DESCRIPTION
01	58T-40GR20-4MP	FILTER HEAD WELDMT
02	58T-3BOWL	FILTER BOWL
03	583E-25SD	ELEMENT, FILTER
04	4010-251V7	O-RING, VITON SZ 251
05	4010-223V7	O-RING, VITON SZ 223

- NOTES:
- LUBE ALL O-RINGS, O-RING SEAL SURFACES, THREADED CONNECTIONS WITH AN OXYGEN COMPATIBLE LUBRICANT (CHRISTO-LUBE MCG-111 OR EQUAL).
 - TORQUE REQUIREMENTS:
BONNET TO BODY 150 FT-LBS

TEE TYPE FILTER ASSEMBLY
 316 SST HEAD AND BOWL
 SST WIRE FILTER
 7500 PSIG MAX PRESSURE
 PROOF PRESSURE 150%

OPTIONAL
 D4MP-1/4 MP DP PORTS

F1526-25SDV-D4MP

58 SERIES
 BOWL SIZE-3
 GRAYLOC 2 1/2 GR20

V-VITON O-RINGS
 D -3000 PSID
 COLLAPSE RATING
 25S -10 NOM/25 ABS
 MICRON RATING
 304 SST

REV.	DATE	CHG BY	DESCRIPTION OF CHANGE
1	12-19-24	PTS	INITIAL RELEASE

REVISION HISTORY

MATERIAL	
FINISH	

ALL PARTS MUST BE CLEANED FOR OXYGEN SERVICE PER ASTM SPEC G93. GLOVES MUST BE WORN DURING PART HANDLING.

UNLESS OTHERWISE SPECIFIED:
 A ± .02 REMOVE ALL BURRS
 B ± .01 DIMENSIONS IN INCHES
 C ± .005 ISO / ASME Y14.5
 ANGLE ± 1°
 CORNER BREAKS .005-.020
 FILLET RADI .005-.020
 SURFACE ROUGHNESS: 32 ✓
 THREADS: CLASS 2
 THREAD LENGTHS ARE FULL THREAD
 DO NOT SCALE PRINTED DRAWING

SCALE: 1:2

DRAWN BY: _____ APPROVED BY: _____

DESCRIPTION
ASSEMBLY FILTER

CAGE CODE 4FX47	PART NUMBER F1526-25SDV-D4MP	SHEET 1	OF 1	SIZE C
--------------------	---------------------------------	------------	---------	-----------



THIS DOCUMENT AND ITS CONTENT IS PROPERTY OF CHASE FILTERS AND COMPONENTS. IT MAY NOT BE COPIED, REPRODUCED, PROVIDED, OR REVEALED TO ANY OTHER PARTY WITHOUT WRITTEN AUTHORIZATION.