


1	5-31-22	PTS	CONCEPT
REV.	DATE	CHG BY	DESCRIPTION OF CHANGE
REVISION HISTORY			
MATERIAL			 <small>CHASE FILTERS & COMPONENTS NEWPORT NEWS, VIRGINIA 23607</small>
316 SST			
FINISH			<small>THIS DOCUMENT AND ITS CONTENT IS PROPERTY OF CHASE FILTERS AND COMPONENTS. IT MAY NOT BE COPIED, REPRODUCED, PROVIDED, OR REVEALED TO ANY OTHER PARTY WITHOUT WRITTEN AUTHORIZATION.</small>
<small>ALL PARTS MUST BE CLEANED FOR OXYGEN SERVICE PER ASTM SPEC G93. GLOVES MUST BE WORN DURING PART HANDLING.</small>			
<small>UNLESS OTHERWISE SPECIFIED: Ø ± .02 REMOVE ALL BURRS .00 ± .01 DIMENSIONS IN INCHES .000 ± .005 ISO / ASME Y14.5 ANGLE ± 1° CORNER BREAKS .005-.020 FILLET RADI .005-.020 SURFACE ROUGHNESS: R_a ✓ THREADS: CLASS 2 THREAD LENGTHS ARE FULL THREAD DO NOT SCALE PRINTED DRAWING</small>			
<small>SCALE:</small>			
<small>DRAWN BY:</small>		<small>APPROVED BY:</small>	
DESCRIPTION ASSEMBLY FILTER			<small>SIZE</small> C
<small>CAGE CODE</small> 4FX47	<small>PART NUMBER</small> F1481-8.00-40		
<small>THIRD ANGLE PROJECTION</small>		<small>SHT.</small> 1 OF 1	